# 395 Nutdriver, 15 x 125 mm

## Kraftform Plus – Series 300



| | | | |
|---|---|---|---|
| **EAN:** | 4013288004888 | **Size:** | 237x37x37 mm |
| **Part number:** | 05029450001 | **Weight:** | 180 g |
| **Article number:** | 395 | **Country of origin:** | CZ |
| | | **Customs tariff number:** | 82054000 |

- Nutsetter for hexagon head screws
- Multi-component Kraftform handle for fast and ergonomic screwdriving
- Handle markings simplify finding and sorting of tools
- Hexagonal anti-roll feature against rolling away
- Chrome-plated

High quality nutsetter by Wera. Multi-component Kraftform handle for high working speeds and particularly ergonomic screwdriving. Kraftform Plus: hard gripping zones for high working speeds whereas soft zones ensure high torque transfer. Hexagonal anti-roll feature prevents any rolling away and handle markings make for simplified finding and sorting of the tool; for hexagon head screws.

**Web link**
https://products.wera.de/en/screwdrivers_kraftform_plus__series_300_395.html

Wera - 395
05029450001 - 4013288004888

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de



Kraftform Plus screwdrivers - ergonomics you can grasp. They relieve the entire hand-arm system even when used intensively. Along with other technical and product advantages such as the Lasertip for a secure fit in the screw head, Kraftform screwdrivers are the ideal choice whenever manual screwdriving jobs are concerned.

### Kraftform



The basic idea for the prototype of the Kraftform handle - that the hand should dictate the design - has, right through to today, proved to be correct. In cooperation with the internationally recognised Fraunhofer IAO Institute, Wera developed a screwdriver handle designed to match the shape of the human hand as long ago as the 1960s. After a long development phase, the Wera Kraftform handle was launched to the market in 1968. It has been optimised through the years with new technologies, but has kept its proven shape. After all, the human hand has not changed either.

### Rapid hand repositioning



The hard materials used for the handle ensure rapid hand repositioning without any danger of the skin "sticking" to the handle. The surrounding hard zones with large diameters glide like wheels through the hand.

### Large contact area



The large contact area - with particularly high friction to the soft zones - results in high torque transfer without any bruising from the edges.

### Non-roll feature



The hexagonal non-roll feature prevents any rolling away at the workplace.

### Identification marking




The screw symbol and tip size identification markings on the handle make it easier to find the right screwdriver in the tool case, or at the workplace.

**Web link**
https://products.wera.de/en/screwdrivers_kraftform_plus__series_300_395.html

Wera - 395
05029450001 - 4013288004888

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

Further versions in this product family:

| |  mm |  mm |  mm |  mm |  inch |
|---|---|---|---|---|---|
| 05028205001 | 3.0 | 125 | 98 | 5.0 | 5" |
| 05028210001 | 3.5 | 125 | 98 | 6.1 | 5" |
| 05028215001 | 4.0 | 125 | 98 | 6.9 | 5" |
| 05028220001 | 4.5 | 125 | 98 | 7.1 | 5" |
| 05028225001 | 5.0 | 125 | 98 | 8.1 | 5" |
| 05028230001 | 5.5 | 125 | 98 | 8.1 | 5" |
| 05029405001 | 6.0 | 125 | 98 | 9.1 | 5" |
| 05029410001 | 7.0 | 125 | 105 | 11.0 | 5" |
| 05029415001 | 8.0 | 125 | 105 | 12.1 | 5" |
| 05029420001 | 9.0 | 125 | 105 | 13.1 | 5" |
| 05029425001 | 10.0 | 125 | 112 | 14.1 | 5" |
| 05029430001 | 11.0 | 125 | 112 | 16.0 | 5" |
| 05029435001 | 12.0 | 125 | 112 | 17.1 | 5" |
| 05029440001 | 13.0 | 125 | 112 | 18.1 | 5" |
| 05029445001 | 14.0 | 125 | 112 | 19.1 | 5" |
| **05029450001** | **15.0** | **125** | **112** | **21.0** | **5"** |

**Web link**
https://products.wera.de/en/screwdrivers_kraftform_plus__series_300_395.html

Wera - 395
05029450001 - 4013288004888

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de