847 HSS Combined Tap Bits, 6.8 x 51 mm

Bit Sets for Special Applications



EAN:	4013288101549	**Size:**	117x65x14 mm
Part number:	05104644001	**Weight:**	18 g
Article number:	847 HSS	**Country of origin:**	CN
		Customs tariff number:	82075060

- Hex shaft for very good power transfer
- Finely-tuned material elasticity for great durability
- Very good centring properties
- Perfect chip removal
- Precise return movement

High quality combination tapping drill bits for drilling, tapping and deburring. Made out of high speed steel (HSS). A finely-tuned material elasticity provides for great durability. The very good centring properties, perfect chip removal and a low tilt risk ensure pleasant working. The hexagonal shaft ensures very good power transfer. Drive: ¼" hexagon, suitable for holders with take-up as per DIN ISO 1173-D 6.3.

Web link
https://products.wera.de/en/bits_holders_adaptors_and_sets_bit_sets_bit_sets_for_special_applications_847_hss.html

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

Combination drill bits



Combination drill bits • Application: Core-hole drilling, tapping and deburring in one operation • ¼" drive suitable for holders as per DIN 3126-D 6.3 (ISO 1173) • Hexagon shaft for very high torque transfer • HSS = high speed steel • Finely adjusted material elasticity for long service life • Excellent centring properties • Straightforward cutting • Perfect chip removal • Low jamming risk • Precise return control

Further versions in this product family:

	mm	mm	mm	
05104640001	2.5	12.00	36.0	M 3
05104641001	3.3	12.00	39.0	M 4
05104642001	4.2	12.00	41.0	M 5
05104643001	5.0	12.00	44.0	M 6
05104644001	**6.8**	**12.00**	**51.0**	**M 8**
05104645001	8.5	12.00	59.0	M 10

Web link
https://products.wera.de/en/bits_holders_adaptors_and_sets_bit_sets_bit_sets_for_special_applications_847_hss.html

Wera - 847 HSS
05104644001 - 4013288101549

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de