853/4 ACR® SL bits with sleeve, magnetized, PH 2 x 200 mm

Bits for Phillips Screws



EAN:	4013288163196	**Size:**	200x7x7 mm
Part number:	05203914001	**Weight:**	35 g
Article number:	853/4 ACR® SL	**Country of origin:**	CZ
		Customs tariff number:	82079030

- For Phillips screws
- ACR (anti cam-out feature) to prevent any slipping out of the screw head
- Permanently magnetized, thus screws can be held securely on the tip of the bit
- With plastic sleeve, protects components from being damaged when screwdriving
- 1/4" hexagon drive (Wera connecting series 4)

High quality bits with rough ribs (anti cam-out feature, ACR) to prevent any slipping out of the screw head, permanently magnetized, thus screws can be held securely on the tip of the bit; with plastic sleeve, protects components from being damaged when screwdriving. Tough viscous for universal use. ¼" hexagon, suitable for holders as per DIN ISO 1173-F 6.3.

Web link
https://products.wera.de/en/bits_holders_adaptors_and_sets_the_range_of_bits_bits_for_phillips_screws_853_4_acr_sl.html

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

853/4 ACR® SL bits with sleeve, magnetized, PH 2 x 200 mm

Bits for Phillips Screws

ACR®-Bits



ACR® stands for "anti-cam-out ribs". ACR® bits have ribs at the drive tip that protect against slipping out of the screw head. It is recommended that ACR® bits are matched with ribbed ACR® screws for maximum effect. ACR® is a registered trademark of Phillips Screw Company.

With sleeve



With plastic sleeve, protects components from being damaged when screwdriving

Magnetic



Permanently magnetized, thus screws can be held securely on the tip of the bit.

Further versions in this product family:

		mm	inch	mm
05323780001	PH 2	50	2"	5.2
05323781001	PH 2	90	3 1/2"	5.2
05203913001	PH 2	150	6"	5.2
05203914001	**PH 2**	**200**	**8"**	**5.2**

Web link
https://products.wera.de/en/bits_holders_adaptors_and_sets_the_range_of_bits_bits_for_phillips_screws_853_4_acr_sl.html

Wera - 853/4 ACR® SL
05203914001 - 4013288163196

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de