SEMS SCREW TERMINALS


SPECIFICATIONS


Terminal: .032 (.81) Brass, Matte Tin Plate Screw & Washer: Steel, Nickel Plate

SEMS Screw Terminals provide quick and secure attachment of wire leads. SEMS screw has captivated, free spining lock washer, eliminated twisting of wire when tightening lead to terminal. Washer will rise with head of screw when unscrewed.










SEMS SCREW ONLY









CAT.	NO.	8189-SEMS	(Screw Supplied Unassembled)
CAT.	NO.	7702-SEMS	(Screw Installed & Captivated)

CAT. NO.	THREAD	LENGTH
9920	6-32	.250 (6.4)
9923	M3	.188 (4.8)








SEMS SCREW	440 11.2] .197 [5.0]
.276	




6-32 THREAD		M3 THREAD
CAT. NO.		CAT. NO.
7681-SEMS	Screw Supplied Unassembled	7698-SEMS
7693-SEMS	No Screw Supplied	7696-SEMS

6-32 THREAD CAT. NO.		M3 THREAD CAT. NO.
8191-SEMS	Screw Supplied Unassembled	7771-SEMS
7701-SEMS	No Screw Supplied	7772-SEMS






6-32 THREAD		M3 THREAD
CAT. NO.		CAT. NO.
7690-SEMS	Screw Supplied Unassembled	7699-SEMS
7692-SEMS	Screw Installed & Captivated	7695-SEMS






6-32 THREAD		M3 THREAD
CAT. NO.		CAT. NO.
8190-SEMS	Screw Supplied Unassembled	7761-SEMS
7700-SEMS	No Screw Supplied	7762-SEMS








6-32 SEMS SCREW




CAT. NO. 8195-SEMS (Screw Supplied Unassembled) CAT. NO. 7775-SEMS (Screw Installed & Captivated)

CAT. NO. 8198-SEMS (Screw Supplied Unassembled) CAT. NO. 7778-SEMS (Screw Installed & Captivated)







.250



CAT. NO. 8197-SEMS (Screw Supplied Unassembled) CAT. NO. 8199-SEMS (Screw Installed & Captivated)

