867/22 IP TORX PLUS® bits, 8 IP x 80 x 3 mm



EAN:	4013288113436	**Size:**	80x6x5 mm
Part number:	05344281001	**Weight:**	10 g
Article number:	867/22 TORX PLUS®	**Country of origin:**	CZ
		Customs tariff number:	82079030

- For TORX PLUS® screws
- Tough for hard materials
- HIOS drive 5 mm

High quality bits for recessed TORX PLUS® screws. Tough viscous for universal use. Drive: HIOS 5 mm.

Web link

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

TORX PLUS®



Compared with the "normal" TORX® profile, the elliptical instead of circular profile enlarges the 6 flanks that transfer torque between the tool and the screw. This means that the force applied when screwdriving is spread across a larger surface area. Higher torque is transferred and, in addition, the service life of the screw and tool are lengthened. The so-called centre-lock screws on cutting tools represent a typical use of this type of screw profile. The thermal influences on such holders for carbide insert tips often "bake" the retaining screws so firmly that it is important to have a profile that considerably enhances the loosening torque capability of the screws. For this reason a torque-stable screw profile is necessary to avoid any possible damage to the screw and to exclude the possibility of an otherwise costly machine downtime.

5 mm HIOS direct drive



HIOS, 5mm, Wera Series 22. Drive: For direct machine drive. Suitable for: CL-6000, CL-6500, CL-7000, SS-6500, SS-7000, L-6500, CD-6000, CD-7000, VZ-1820 (100 V), VZ-3012 (100 V) (incl. PS-Typ).

Web link

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de