

TECHNICAL DATA SHEET

Part No. 111-00300
Article No. 111-00300
Type MBT20XHFC



HellermannTyton's MBT Ties are fabricated from corrosion-resistant 316 stainless steel and have a protective polyester coating. Stainless tie design includes a non-releasable locking feature for secure applications. Polyester coating provides smooth edges to make it safer for installers' hands and eliminates contact corrosion between dissimilar materials.

Material	Stainless Steel (SS316L), Polyester (SP)
Operating Temperature	-112°F to +1000°F (-80°C to +538°C)
Flammability	Non-burning (except coating), low smoke in accordance with CSA C22.2 No. 62275:21
Halogen Free	Yes
UV Resistant	Yes
Use Conditions	For Indoor and Outdoor Use
Color	Black (BK)
Pkg. Qty.	50
Carton Qty.	500
Customs Number	7326908695

Length (imperial)	20.5 "
Length (metric)	521 mm
Max. Bundle Diameter (imperial)	5.98 "
Max. Bundle Diameter (metric)	152 mm
Min. Tensile Strength (imperial)	364 lbs
Min. Tensile Strength (metric)	1620 N
Thickness (imperial)	0.01 "
Thickness (metric)	0.38 mm
Width (imperial)	0.48 "
Width (metric)	12.3 mm

