

# TECHNICAL DATA SHEET

**Part No.** CTT20R9C2  
**Article No.** 112-51919  
**Type** CTT20R



HellermannTyton clamp tie has triangular shaped tabs extending beneath the head for optimal surface contact and complete circumferential compression to 360 degrees. The bent tail design allows quick and simple installations by hand. The clamps are recommended for soft rubber hose applications including fuel, water, and air vacuum lines.

|                              |                                  |
|------------------------------|----------------------------------|
| <b>Material</b>              | Polyamide 6.6 (PA66)             |
| <b>Operating Temperature</b> | -40°F to +185°F (-40°C to +85°C) |
| <b>Flammability</b>          | UL 94 V-2                        |
| <b>UV Resistant</b>          | No                               |
| <b>Use Conditions</b>        | For Indoor Use Only              |
| <b>Color</b>                 | Natural (NA)                     |
| <b>Pkg. Qty.</b>             | 100                              |
| <b>Carton Qty.</b>           | 10000                            |
| <b>Customs Number</b>        | 3926909988                       |

|                                         |                 |
|-----------------------------------------|-----------------|
| <b>Length (imperial)</b>                | 3.94 "          |
| <b>Length (metric)</b>                  | 100 mm          |
| <b>Max. Bundle Diameter (imperial)</b>  | 0.51 "          |
| <b>Max. Bundle Diameter (metric)</b>    | 13.0 mm         |
| <b>Min. Tensile Strength (imperial)</b> | 20 lbs          |
| <b>Min. Tensile Strength (metric)</b>   | 90 N            |
| <b>Serration Side</b>                   | Inside Serrated |
| <b>Thickness (imperial)</b>             | 0.043 "         |
| <b>Thickness (metric)</b>               | 1.1 mm          |
| <b>Width (imperial)</b>                 | 0.10 "          |
| <b>Width (metric)</b>                   | 2.5 mm          |

