

# TECHNICAL DATA SHEET

**Part No.** T18RWPM9M4  
**Article No.** 126-00603  
**Type** T18RWPM



Wing design helps stabilize the tie in high vibration applications. One-piece mounting ties offer a complete solution by both bundling cable and simultaneously providing a mounting solution. HellermannTyton's one-piece mounting ties offer the ideal combination of high specification materials and superior design to suit the mounting and bundling needs of complex applications.

|                              |                                  |
|------------------------------|----------------------------------|
| <b>Material</b>              | Polyamide 6.6 (PA66)             |
| <b>Operating Temperature</b> | -40°F to +185°F (-40°C to +85°C) |
| <b>Flammability</b>          | UL 94 V-2                        |
| <b>UV Resistant</b>          | No                               |
| <b>Use Conditions</b>        | For Indoor Use Only              |
| <b>Color</b>                 | Natural (NA)                     |
| <b>Pkg. Qty.</b>             | 1000                             |
| <b>Carton Qty.</b>           | 10000                            |
| <b>Customs Number</b>        | 3926909988                       |

|                                          |               |
|------------------------------------------|---------------|
| <b>Fixation Method</b>                   | Arrowhead     |
| <b>Height (imperial)</b>                 | .23 "         |
| <b>Height (metric)</b>                   | 5.80 mm       |
| <b>Length (imperial)</b>                 | 4.5 "         |
| <b>Length (metric)</b>                   | 113.0 mm      |
| <b>Max. Bundle Diameter (imperial)</b>   | 0.87 "        |
| <b>Max. Bundle Diameter (metric)</b>     | 22.0 mm       |
| <b>Min. Tensile Strength (imperial)</b>  | 18 lbs        |
| <b>Min. Tensile Strength (metric)</b>    | 80 N          |
| <b>Mounting Hole Diameter (imperial)</b> | 0.19 - 0.22 " |
| <b>Mounting Hole Diameter (metric)</b>   | 4.8 - 5.6 mm  |
| <b>Panel Thickness (imperial)</b>        | 0.06 - 0.13 " |
| <b>Panel Thickness (metric)</b>          | 1.52 - 3.2 mm |
| <b>Thickness (imperial)</b>              | 0.043 "       |
| <b>Thickness (metric)</b>                | 1.1 mm        |
| <b>Width (imperial)</b>                  | 0.1 "         |
| <b>Width (metric)</b>                    | 2.5 mm        |

RoHS✓

