

TECHNICAL DATA SHEET

Part No. 184-11013
Article No. 184-11013
Type SLHD1X1



HellermannTyton High-Density Slotted Wall Wiring Duct features narrow fingers equaling a 2-to-1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.

Material	Polyvinylchloride (PVC)
Operating Temperature	+122°F (+50°C)
Flammability	UL 94 V-0
Halogen Free	No
UV Resistant	No
Use Conditions	For Indoor Use Only
Color	Gray (GY)
Pkg. Qty.	140.0 ft
Carton Qty.	140.0 ft
Customs Number	3925900000

Fixation Method	Non-Adhesive
Height (imperial)	1.06 "
Height (metric)	26.92 mm
Length (imperial)	7 ft
Length (metric)	2.13 m
Mounting Hole Centers (imperial)	2.00 "
Mounting Hole Centers (metric)	50.80 mm
Width (imperial)	1.00 "
Width (metric)	25.40 mm
Width 3 (imperial)	.16 "
Width 3 (metric)	4.1 mm
Width 4 (imperial)	.40 "
Width 4 (metric)	10.2 mm
Width 5 (imperial)	.75 "
Width 5 (metric)	19.1 mm

